

3S 10A 12V 18650 Lithium Battery Charger Board Protection Module

slug-3s-10a-12v-18650-lithium-battery-charger-board-protection-module



TECHNICAL SPECIFICATIONS & SUMMARY

[Lithium Battery Protection Board] In 3S 10A 12V 18650 Lithium Battery Charger Board Protection Module, 3S stands for 3 18650 batteries or polymer lithium battery series combination. With 10.8V rated voltage for polymer battery, 11.1V 18650 or 3.7V lithium battery rated voltage and 12.6V lithium battery can be charged. And discharge 10A (referring to the maximum discharge current limit) Lithium battery protection board it also Comes with over-charge, over-discharge, over-current, short circuit protection. Formula Expansion : 1C battery expansion, 2000 capacity is equal to 2AH * 1 = 2A upper limit of current. 3C battery expansion, 2000 capacity equal to 2AH * 3 = 6A upper operating current. If the battery gets heat, does not apply that battery, such a situation cannot be long-term use, the battery will soon be damaged. Notes : 1: strictly according to the drawing wiring 0 V (B), 3.7 V (B1), 7.4 V (B2), 11.1 V (B +), not intentionally short circuit! 2: Once you have charged the first line, it will have output. 3: When connecting three battery groups, please make sure that the voltage of each battery group, if

UNIT PRICE (EX. GST)

Rs. 49

WITH 18% GST

Rs. 58

In stock: 0 units - HSN: 85044090
Order online at uniksystem.in for bulk pricing.