

ESP8266 WiFi 5V 1 Channel Relay Module Good Quality

Slug: esp8266-wifi-5v-1-channel-relay-module

(placeholder)

FRONT

(placeholder)

BACK

(placeholder)

DETAIL

(placeholder)

PINOUT

TECHNICAL SPECIFICATIONS & SUMMARY

[Relay Module] General Info : Onboard ESP8266 WIFI module, AP mode can be connected at the same time 5 client The module has two ways to work: (i) mobile phone directly mounted on the WIFI module; (ii) mobile phone and WIFI module also carried on the router. How to use : Onboard ESP8266 WIFI module has three operating modes: STA (client), AP (hot), STA + AP (client + hot), according to the work of the module to select the corresponding WIFI module mode of operation The module needs to use the serial debugging software on the computer and USB to TTL module to send AT commands to configure the WIFI module, USB to TTL module RX, TX, GND pin, then the module on the TX, RX, GND pin, IN +, IN - 5V power supply. Usage Instructions 1) Hardware Connection: Insert the pre-programmed ESP-01/01S module into the onboard 2x4 pin female header (as shown in the diagram below). 2) Power Supply : Connect a DC 5V-12V power source to the module, with the positive terminal to VCC and the negative terminal to GND. 3) Mobile WiFi Connection : Open your phone's

UNIT PRICE (EX. GST)

Rs. 249

WITH 18% GST

Rs. 294

In stock: 10 units - HSN: 85044090

Order online at uniksystem.in for bulk pricing.