

JBD 3-4S/100A Smart BMS For LiFePO4 (LFP) batteries

Slug: jbd-3-4s-100a-smart-bms-for-lifepo4-lfp-batteries



TECHNICAL SPECIFICATIONS & SUMMARY

[Lithium Battery Protection Board] JBD Smart BMS 3-4S 100A (DP04S014) Charge and discharge are both at the same port Product Data Sheet Cell specifications: 3~4 strings of LiFePO4 battery Continuous current: 100A Balance detect Voltage 3.8 Interface type: Charge and discharge are both at the same port Charging voltage: 3.6V*Number of strings Cell voltage range: 2.30~3.75V Continuous charging current: 100A Continuous discharging current: 100A The JBD SMART BMS 100A DP04S014 (3-4S) is a compact and powerful Battery Management System designed for lithium-ion and LiFePO4 battery packs with 3 to 4 series cells. It supports a continuous discharge current of 100A, making it suitable for high-power applications such as electric vehicles, portable power systems, and energy storage solutions. This BMS provides essential protection features including overcharge, over-discharge, overcurrent, short circuit, and temperature management to ensure safe and reliable battery operation. With active cell balancing, it maintains voltage consistency across cells. It also supports

UNIT PRICE (EX. GST)

Rs. 3,599

WITH 18% GST

Rs. 4,247

In stock: 10 units - HSN: 85044090
Order online at uniksystem.in for bulk pricing.