

Pro Mini ATMEGA328P 3.3V/8M

Slug: pro-mini-atmega328p-3-3v-8m



TECHNICAL SPECIFICATIONS & SUMMARY

[Arduino Boards] This is Pro Mini ATMEGA328P 3.3V/8MHz is a 3.3V Arduino running the 8MHz bootloader. Pro Mini ATMEGA328P come with connectors so that you can solder connector or wire with any orientation you need. It's a great board that will get you up and running quickly. The Arduino Pro series is meant for users that understand the limitations of system voltage (3.3V), lack of connectors, and USB off board. The Pro Mini is a microcontroller board base on the ATmega328. It has 14 digital input/output pins (of which 6 can be used as PWM outputs), 6 analog inputs, an on-board resonator, a reset button, and holes for mounting pin headers. A six pin header can be connected to an FTDI cable to provide USB power and communication to the board. The Pro Mini is intended for semi-permanent installation in objects or exhibitions. The board comes with headers, allowing the use of various types of connectors or direct soldering of wires. The pin layout is compatible with the Mini Arduino. Features : 8 analog input port: A0 ~ A7. A pair of TTL level serial port

UNIT PRICE (EX. GST)

Rs. 199

WITH 18% GST

Rs. 235

In stock: 10 units - HSN: 85423100
Order online at uniksystem.in for bulk pricing.