


XH-M139 50Wx2+100W 2.1 Channel Digital Subwoofer Amplifier Board 12V-24V

slug: tp6811662-50wx2+100w-2.1-channel-digital-subwoofer-amplifier-board-12v-24v



TECHNICAL SPECIFICATIONS & SUMMARY

[Amplifier Board] DC12-24V 2.1 Channel Digital Subwoofer Power Amplifier Board adopts two high-quality digital amplifier chips. Sound quality is very good, high efficiency and amplifying power. 50W x 2+100W 2.1 channels (left/right channel and subwoofer channel), high efficiency and low-heat. Users can adjust the volume by themselves easily. It is powered by DC 12-24V, wide input voltage. Features: Adopts two high-quality digital amplifier chips. Good sound quality, high efficient device and power amplifying feature. 50W x 2+100W 2.1 channels(left/right channel and subwoofer channel), high efficiency and low-heat. Powered by DC 12-24V, wide input voltage. User can adjust the volume by themselves easily. Applicable speaker impedance: 4-8 ohm. Just connect the power supply and loudspeaker box, enjoy pure digital music!. Specification Supply Voltage DC 12-24V Main Chip CS3835E0x 2 Channel Type 3 Channels(Left Channel, Right Channel, Subwoofer) Output Power 50W x 2 + 100W x 1 Subwoofer Output Match 4-8 ohm Audio Output Terminals Frequency Response Range

UNIT PRICE (EX. GST)

Rs. 649

WITH 18% GST

Rs. 766

In stock: 10 units - HSN: 85285900

Order online at uniksystem.in for bulk pricing.